

MANUFACTURE STANDARD, MANUFACTURE RELIANCE

# RT-1904C

## Semi-auto Chemistry Analyzer



### Features

- Easy Windows operation system with mouse, large color LCD display
- Reagent open system supports flow cell and cuvette mode, close system on request
- Analytical modes include kinetic, fixed time, bichromatic end point with or without reagent blank or sample blank, linear or non-linear calibration
- Real-time curve monitoring enhances the reliability of result
- Large memory, up to 160 test protocols can be programmed
- Powerful QC function: Westguard Multi-rule, Levey Jennings plot, 2 controls per test
- Auto power-on self-check
- Additional lamp saving
- Multiform result output including patient comprehensive report
- Software optional for date management in PC
- Easy maintenance, no service engineers required to change lamp, tube etc



# RT-1904C

## Semi-auto Chemistry Analyzer

Test Report		
General		Date: 28/10/2003
Sample No: 03	Name: XXX	Sex: Male Age: 28
Dept.: xx	Patient No: 003	Sender: XXX
Test	Result	REF Range
ALT	39.311U/L	0.00-40.00
AST	110.239U/L	0.00-37.00
TP	98.225 g/L	46.00-87.00
ALB	52.055 g/L	38.00-44.00



### Reaction curve




### Programming




### Test list

Test	Result	REF	Unit	Flag
ALT	39.311	0.00-40.00	U/L	
AST	110.239	0.00-37.00	U/L	
TP	98.225	46.00-87.00	g/L	
ALB	52.055	38.00-44.00	g/L	

### Calibration



### Quality control



### Patient data management

No.	Name	Sex	Age	Dept.	Report mode
001	John	M	28	000	Print
002	John	M	28	000	Print

## Technical Specifications

Photometric range	-0.500-3.000Abs
Resolution	0.001Abs(displayed), 0.0001Abs(calculated)
Light source	Halogen lamp, 6V/10W
Wavelengths	340,405,500,546,578,620,670nm, 1 more filter optional
Wavelength accuracy	±1nm
Band width	8nm
Aspirate Volume	100-3000ul
Cross Contamination Rate	<0.1%
Memory	160 test protocols, minimum 500 test result
Interface	RS-232,PSTN (optional)
Flow cell	25µl Metal-quartz flow cell
Cuvette mode	12.5mmx12.5mm cuvette optional
Temperature control	25℃,30℃,37℃ ±0.1℃
Display	7" color LCD
Input	External mouse and optional external keyboard
Output	Built-in printer or external printer (optional)
Net weight	8KG
Dimensions L × W × H (mm)	460 x 330 x 140
Power supply	AC 110V/220V±10%, 50/60Hz

## Rayto Life and Analytical Sciences Co.,Ltd.

2nd Floor, 5th Building, Software Park, NO.2, Gaoxinzhong  
3rd Road, High-tech Industrial Park, Nanshan,  
Shenzhen 518057, P.R. China  
Tel: +86(755)86168182 Fax: +86(755)86168796  
Email: info@rayto.com

